



www.xegermany.de

X^e PS 8 Technical Data

- Solar Energy Transmission 77%
- Solar Energy Reflection - Exterior..... 08%
- Solar Energy Absorption 14%
- Visible Light Transmission..... 87%
- Visible Light Reflection - Exterior 09%
- Interior 10%
- UV Transmission <1%
- Shading Coefficient (b Value) 0.92
- Emissivity 0.84
- U-Value (EN 673 W/m²K) 5.6
- Glare Reduction 1%
- Coefficient of Total Energy Transmission (g Value) 0.80
- Thickness without Liner 224
- Total Solar Energy Rejected..... 20%

Characteristics & Benefits

- **Safety Film: Safe glass breakage conformity with EN 12 600**
- Excellence Transparency
- Nearly invisible, once installed.
- UV protection only in the adhesive layer. Minimal protection against fading of textiles, furniture, and works of art.
- **Scratch resistance coating:** Durability of film due to easier cleaning and maintenance. Faster and easier installation.
- **High-end, water soluble, extremely heat resistant adhesive with immediate agglomerating power when pressing:** Faster and easier removal of adhesive residues on the window pane after peeling off the film (time saving).

Features

Tensile Strenght	-Machine direction	204 N/mm²
	-Transverse direction	167 N/mm²
Yeild Strength	-Machine direction	104 N/mm²
	-Transverse direction	108 N/mm²
Elongation at Break	-Machine direction	86%
	-Transverse direction	108%
Elongation at Yeild	-Machine direction	7%
	-Transverse direction	7%